

Get the most out of Jabil Engineered Materials Powder

... ..> , ~-%p>~L†YsL~HY^>A L~
psnp †Y>S¥~...>^%5pL~HL^>s~L%Y , ~>-H~L~BL L~"~%N~BL~T~S~> , E~N~^%o\$H AYs"~...>^%o) Y~...L~
T~S~p~s~n~... %Ass L%o >yL~/~ Z , sHL>N~ , ..L~ %oY~BLH~>%o~%o~L~s~n~ / ~...s~L~%o

Jabil Engineered Materials Recommended Print Settings



Print Temperature

- />~"~ LH^5L} ...
- /S%o~^5L} ...
- ~ ¥s~HL^5L} ...
- † LLH^5L} ...

Layer Thickness

~ } }



Fill Settings

- † s~&>%o~/, E L~
- † s~3B>~3...Bs~n~
- † s~3B>~ , Y~"

Colors

* >Y^>: psL

Applications

- † Y~B , ~>~... , " , #¥..L%
- ~ , } ...L~nL , } L^~L%
- ~& E~"L} ..L^>Y~L~HYB~"E , ~y
- ~ >%L~p , Y%on%
- ~Z , Y%on%~HL~B , %L%

Advantages

- ~Z snpL^~%oQ~L%op>~"/
- ~/ , HYBL%bL~%o...>^%E sp^>~L~BL L~"~%N~BL~T~S~>
- ~ , , ^~%Ass¥
- ~2L > CL ¥S%o" , ..B~..L~N~ } >>BL

Questions? Contact us: JabilAdditive@jabil.com

/ YL~ , ~pL~>nL~c>~L~¥ , N...s~L~%o~H~...>~"nL , } L^~L%~pL~nsL~... , BL%o.>^>~
>A , Y~"

PA 4000
Material

A

w

A

Subscribe
to the Jabil
Additive
Newsletter

