J422-S High Performance 6th Gen Inte[®] Xeon[®] 2U Dual Socket MHS Rackmount Server

Elevateyour most demanding workloads with a modern platform designed specifically to

power your artificial intelligence (AI), Machinelearning (ML), high performance computing

(HPC), and Fintech workloads. With high performance expandability and flexibility in mind,

this M.7 7.6 (i)(2l)01 (y)-1.5 (c)10 (o)-1e1-11 (b)6.7 (i)0. (o)-1.4 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (t)-15 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (t)-15 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (t)-15 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (t)-15 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (t)-15 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (n)8..9 ()7r7 (d)7.8 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (d)0.6 (e)4 6 (rk)-7 (i)0.7 (n)8..9 ()0.7 (n)8..9 ()0.(M.7 (r)7.1 (m)0.7 ()0.5 (n)8..9 (n)8

Contact your Jabil Sales Representative for more information.

SPECIFICATIONS

CHASSIS

FRONT I/O

Form Factor

2U Rackmount

Model

J422-S (SFF)

DIMENSIONS

PROCESSOR

CPU

• 2x 6th Generation

SYSTEM MEMORY

Fans

Contact your Jabil Sales Representative for more information.